

Bảng thông số sản phẩm

Thông số kỹ thuật



Easy9 miniature circuit breaker- 1P - 25 A - C curve - 4500 A - 230 V

EZ9F34125

Main

| | |
|---------------------------|--|
| Range | Easy9 |
| Device application | Distribution |
| Product or component type | Miniature circuit-breaker |
| Device short name | Easy9 MCB |
| Poles | 1P |
| Number of protected poles | 1 |
| [In] rated current | 25 A |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Breaking capacity | 4500 A Icn at 230 V AC 50/60 Hz conforming to IEC 60898-1 4500 A Icn at 400 V AC 50/60 Hz conforming to IEC 60898-1 |
| Suitability for isolation | Yes conforming to IEC 60898-1 |

Complementary

| | |
|--|---|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 230 V AC 50 Hz |
| Magnetic tripping limit | 5...10 x In |
| [Ics] rated service breaking capacity | 4.5 kA 100 % x Icn at 230 V AC 50/60 Hz conforming to IEC 60898-1 |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to IEC 60898-1 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60898-1 |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | Without |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 81 mm |

| | |
|--------------------------------|---|
| Width | 18 mm |
| Depth | 66.5 mm |
| Colour | Grey (RAL 7035) |
| Mechanical durability | 10000 cycles |
| Electrical durability | 4000 cycles |
| Connections - terminals | Tunnel type terminal (top or bottom) 1...25 mm ² rigid Tunnel type terminal (top or bottom) 1...16 mm ² flexible |
| Tightening torque | 2 N.m top or bottom |

Environment

| | |
|--|------------------------------|
| Standards | IEC 60898-1 |
| Product certifications | GOST-R |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Pollution degree | 2 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at -25...60 °C |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 108.0 g |
| Package 1 Height | 7.5 cm |
| Package 1 width | 1.8 cm |
| Package 1 Length | 8.5 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 1152 |
| Package 2 Weight | 147.224 kg |
| Package 2 Height | 50 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 1152 |
| Package 3 Weight | 153.016 kg |
| Package 3 Height | 75 cm |
| Package 3 width | 60 cm |
| Package 3 Length | 80 cm |

Offer Sustainability

| | |
|---------------------------------|-----------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |

| | |
|-----------------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |