

Bảng thông số sản phẩm

Thông số kỹ thuật



Enclosure, Resi9 MP, flush mounting, 3 rows of 12 modules, IP40, translucid door, 1 earth + 1 neutral terminal blocks

MIP22312T

Main

Range	Resi9
Product name	Resi9 MP
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12
Nb of horizontal rows	3
Type of door	Translucid
Width	270 mm wall: 294 mm outside:
Height	478 mm wall: 502 mm outside:
Depth	18 mm outside: 80 mm wall: 98 mm total:

Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 20 outgoing 1 neutral (screwed) with 20 outgoing
Distribution block outgoing	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 9 x 10 mm ² for earth 9 x 10 mm ² for neutral 9 x 6 mm ² for earth 9 x 6 mm ² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	76 mm

Colour	Front face: white (RAL 9003) Door: translucent
Market segment	Small commercial Residential
Environment	
Standards	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C
Packing Units	
Unit Type of Package 1	PCE
Package 1 Length	50.2 cm
Number of Units in Package 1	1
Package 3 Width	80 cm
Package 3 Weight	148.016 kg
Package 2 Width	41 cm
Package 2 Height	30 cm
Package 2 Weight	8.501 kg
Number of Units in Package 3	64
Unit Type of Package 3	P12
Package 3 Height	120 cm
Package 3 Length	120 cm
Package 1 Width	29.5 cm
Package 1 Height	9.5 cm
Package 1 Weight	1.939 kg
Number of Units in Package 2	4
Unit Type of Package 2	CAR
Package 2 Length	52.5 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Halogen content performance Halogen free product

Contractual warranty

Warranty 18 months