

Bảng thông số sản phẩm

Thông số kỹ thuật



Socket-outlet, AvatarOn A, complete product, 2P + E, screwless terminals polar white

M3T426UST2_WE

Main

Range of product	AvatarOn A
Product or component type	Socket-outlet
Device presentation	Complete product
Colour tint	White
Outlet poles configuration	2P + E

Complementary

Rated current	16 A at 250 V AC 50...60 Hz
Socket number	1
Clamping connection capacity	2 x 1.5...2 x 4 mm ² for solid cable(s) 2 x 1.5...2 x 4 mm ² for stranded cable(s)
Connections - terminals	Screwless terminals
Material	Polycarbonate cover Polycarbonate base
Device mounting	Flush
Width	70.1 mm
Height	69.3 mm
Depth	30.3 mm
Embedding depth	19 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Ambient air temperature for storage	-5...45 °C
Relative humidity	0...95 %
Operating altitude	< 2000 m
Standards	IEC 60884-1
Product certifications	IEC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	7 cm
Package 1 Length	7 cm
Package 1 Weight	69 g
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Height	9.1 cm
Package 2 Width	13 cm
Package 2 Length	25.5 cm
Package 2 Weight	1.104 kg
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	9.479 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất