

# Product datasheet

Specifications



## USB Charger, Avataron A, 2 port, 2.4A Type A+C, 2S sized , White

M3T\_USB2\_WE

### Main

Range of product	AvatarOn A
Product or component type	USB charger
Mounting mode	Flush-mounted
Integrated connection type	2 USB port 5 V AC/DC, maximum load current: 2.4 A

### Complementary

Device presentation	Complete product
Colour tint	White
Surface finish	Gloss
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
[Ue] rated operational voltage	110...220 V 50...60 Hz
Input power	12 W
Maximum load current with 2 outputs used simultaneously	2.4 A
Material	PC (UL94 V-0)
Screwdriver shape	Philips No 2
Clamping connection capacity	0.5...4 mm <sup>2</sup> for solid or flexible cable(s)
Wire stripping length	12 mm
Height	69.3 mm
Width	46.6 mm
Depth	36 mm
Embedding depth	25 mm

### Environment

Standards	IEC 62368-1
Product certifications	IEC
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	4.7 cm
Package 1 Length	7.0 cm
Package 1 Weight	54.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.1 cm
Package 2 Width	8.9 cm
Package 2 Length	25.5 cm
Package 2 Weight	874.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	7.643 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)