

Product datasheet

Specifications



USB Charger, Avataron A, 1 port, 2.1A, S sized , White

M3T_USB_WE

Main

Range of product	AvatarOn A
Product or component type	USB charger
Mounting mode	Flush-mounted
Integrated connection type	1 USB port 5 V AC/DC, maximum load current: 2.1 A

Complementary

Device presentation	Complete product
Colour tint	White
Surface finish	Gloss
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
[Ue] rated operational voltage	110...220 V 50...60 Hz
Input power	10.5 W
Maximum load current with 2 outputs used simultaneously	2.1 A
Material	PC (UL94 V-0)
Clamping connection capacity	0.5...4 mm ² for solid or flexible cable(s)
Height	69.3 mm
Width	23.1 mm
Depth	35.5 mm
Embedding depth	24.5 mm

Environment

Standards	IEC 62368-1
Product certifications	IEC
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	2.3 cm
Package 1 Length	7.0 cm
Package 1 Weight	35.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	9.1 cm
Package 2 Width	8.9 cm
Package 2 Length	25.5 cm
Package 2 Weight	747.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	240
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	9.614 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)