

Bảng thông số sản phẩm

Thông số kỹ thuật



AvatarOn - 16AX 250V 1Gang Intermediate Switch - WE

E8331M_WD_G19

Main

Product or component type	Switch
Device application	Control
Load type	Inductive Fluorescent lamp Incandescent lamp Resistive
Colour tint	Wood

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50/60 Hz
Switch function	Intermediate
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 3 x 1.5 mm ² for solid cable(s) 3 x 1.5 mm ² for stranded cable(s)
Connections - terminals	Brass terminal
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Flush Surface
Width	86 mm
Height	86 mm
Depth	29.95 mm
Embedding depth	20.25 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %

Operating altitude	2000 m
Environmental characteristic	UV resistant
Standards	GB 16915.1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	8.6 cm
Package 1 Length	2.995 cm
Package 1 Weight	0.001 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất