

# Bảng thông số sản phẩm

Thông số kỹ thuật



## AvatarOn - 16AX 250V 2Gang 1Way Switch with LED - Wood

E8332L1LED\_WD\_G19

### Main

|                           |   |
|---------------------------|---|
| Product or component type | Switch  |
| Device application        | Control   |
| Load type                 | Resistive<br>Fluorescent lamp<br>Incandescent lamp<br>Inductive |
| Colour tint               | Wood  |

### Complementary

|                              |  |
|------------------------------|--|
| Device presentation          | Complete product   |
| Rated current                | 16 AX at 250 V AC 50/60 Hz   |
| Switch function              | 1-pole 1-way   |
| Number of gangs              | 2 gangs  |
| Number of rocker             | 2  |
| Clamping connection capacity | 3 x 2.5 mm <sup>2</sup> for solid cable(s)<br>3 x 2.5 mm <sup>2</sup> for stranded cable(s)<br>4 x 1.5 mm <sup>2</sup> for solid cable(s)<br>4 x 1.5 mm <sup>2</sup> for stranded cable(s) |
| Connections - terminals      | Brass terminal   |
| Local signalling             | Off: LED indicator, LED (amber)  |
| Material                     | Polycarbonate: grid plate<br>Polycarbonate: base<br>Polycarbonate: dolly<br>Polycarbonate: frame<br>Polycarbonate + GF 20 %: actuator  |
| Device mounting              | Flush<br>Surface   |
| Width                        | 86 mm  |
| Height                       | 86 mm  |
| Depth                        | 34.2 mm  |

### Environment

|   |        |
|---|--------|
| IP degree of protection                       | IP20   |
| Maximum ambient air temperature for operation | 45 °C  |
| Operating altitude                            | 2000 m |

|                              |  |
|------------------------------|--|
| Relative humidity            | 0...95 %   |
| Environmental characteristic | UV resistant   |
| Standards                    | SS 227-1<br>BS EN 60669-1<br>IEC 60669-1<br>MS IEC 60669-1 |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 3.4 cm   |
| Package 1 Width              | 8.6 cm   |
| Package 1 Length             | 8.6 cm   |
| Package 1 Weight             | 98.0 g   |
| Unit Type of Package 2       | CAR      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 9.5 cm   |
| Package 2 Width              | 19.0 cm  |
| Package 2 Length             | 19.5 cm  |
| Package 2 Weight             | 1.029 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

Thay thế được đề xuất