

# Bảng thông số sản phẩm

Thông số kỹ thuật



## S-Flexi - 10A 2 Pin Universal Socket - 1.5m - with Shutter - white

F30426USM\_WE\_G19

### Main

Range	S-Flexi
Product or component type	Socket-outlet
Device application	Power supply

### Complementary

Colour tint	White
Quantity per set	1
Type of packing	Plastic bag
Material	PC (polycarbonate)
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50...60 Hz
Network number of phases	1 phase
Outlet standard	IEC 60884-1
Number of gangs	1 gang
Socket number	1
Installation direction	Horizontal/vertical
Device mounting	Flush
Connections - terminals	1.0...2.5 mm <sup>2</sup> screw terminal

### Environment

Standards	IEC
Ambient air temperature for operation	-5...40 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes

---

<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

---

Thay thế được đề xuất