

# Bảng thông số sản phẩm

Thông số kỹ thuật



## S-Flexi - 16A 250V 2 way switch, S size

F50\_2M1\_5\_WE

### Main

Range	S-Flexi
Product or component type	Switch
Wiring device mounting	Flush
Switch function	2-way
Switch application	Electrical circuit control
Load type	Resistive Fluorescent
Colour tint	White

### Complementary

Rated current	16 A at 250 V AC 50/60 Hz
Number of gangs	1 gang horizontal/vertical
Material	PC (polycarbonate)
Clamping connection capacity	0.2...2.5 mm <sup>2</sup> for rigid or stranded cable(s)
Connections - terminals	2 screw terminals
Width	38 mm
Height	23 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	2 cm
Package 1 Length	4 cm
Package 1 Weight	22 g

Unit Type of Package 2	BB1
Number of Units in Package 2	36
Package 2 Height	8 cm
Package 2 Width	12.5 cm
Package 2 Length	18 cm
Package 2 Weight	810 g
Unit Type of Package 3	CAR
Number of Units in Package 3	360
Package 3 Height	21 cm
Package 3 Width	27 cm
Package 3 Length	43 cm
Package 3 Weight	8542 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

Thay thế được đề xuất