

Bell press switch, Vivace, do not disturb and clean up room, aluminium silver

KB31BD_C_AS

Main

| Range | Vivace |
|-------------------------------|----------------------------------|
| Product or component type | Bell press switch |
| Device short name | KB31 |
| Device application | Control |
| Additional switch application | Do not disturb and clean up room |
| Number of rocker | 1 |
| Switch function | 1-way |
| Colour tint | Aluminium silver |

| Complementary | |
|--------------------------------|---|
| Technology type | Electromechanical |
| Device presentation | Complete mechanism |
| Actuator | Push-button |
| Pilot light | Indicator |
| Number of gangs | 1 gang |
| | Aluminium silver |
| Material | Polycarbonate: grid plate Polycarbonate: surround Nylon: base |
| Surface finish | Matt |
| Surface treatment | Painted |
| [Ue] rated operational voltage | 250 V |
| Type of packing | Plastic bag |
| Network type | AC |
| Quantity per set | 1 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A |
| Projecting depth | 8 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |

| Fixing mode | By screw M3.5 |
|---------------------------------------|--|
| Fixing center | 60.3 mm |
| Connections - terminals | Screw terminal |
| Embedding depth | 25 mm |
| Number of terminals | 6 |
| | 10 A at 250 V AC, inductive 10 A at 250 V AC, resistive |
| | 250 V AC |
| Network frequency | 50/60 Hz |
| Contacts material | Brass and phosphor bronze |
| | 6 screw terminals |
| Terminal identifier | N COM |
| | L1 L2 |
| Tightening torque | 0.4 N.m |
| Clamping connection capacity | <= 1.5 mm² for rigid or stranded cable(s) |
| Wire stripping length | 12 mm |
| Width | 86 mm |
| Height | 86 mm |
| Depth | 37 mm |
| | |
| Environment | |
| Standards | MS IEC 60669-1 SS 227 IEC 60669-1 |
| Ambient air temperature for operation | -540 °C |
| Relative humidity | 095 % |
| Operating altitude | 02000 m |
| Environmental characteristic | Indoor use |
| IP degree of protection | IP20 |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.6 cm |
| Package 1 Width | 3.2 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 105.1 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 8 |

9.5 cm

15 cm

19 cm

911 g

CAR

Package 2 Height

Package 2 Width

Package 2 Length

Package 2 Weight

Unit Type of Package 3

| Number of Units in Package 3 | 80 |
|------------------------------|---------|
| Package 3 Height | 21 cm |
| Package 3 Width | 31.5 cm |
| Package 3 Length | 50 cm |
| Package 3 Weight | 8660 g |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

Warranty 18 months

Recommended replacement(s)