

Bảng thông số sản phẩm

Thông số kỹ thuật



Vivace 20A 250V 1gang Double Pole Switch with NeonandEarth, AluminiumSilver

KB31D20NE_AS

- ! **Ngừng sản xuất vào:** 23 tháng một 2021
- ! **Ngừng cung cấp dịch vụ vào:** 24 tháng một 2021

! **Bán dịch vụ hạn chế**

Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device application	Control switch
Additional switch application	On/off switching
Number of rocker	1
Switch function	Double 1-way
Colour tint	Surround: aluminium silver Base: aluminium silver

Complementary

Technology type	Electromechanical
Device presentation	Complete product
Actuator	Rocker
Pilot light	Neon indicator lamp
Number of gangs	1 gang Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Surface finish	Matt
Surface treatment	Painted
[Ue] rated operational voltage	220...250 V
Type of packing	Plastic bag
Network type	AC
Quantity per set	1
Sale per indivisible quantity	1
Rated current	20 A
Projecting depth	8 mm
Device mounting	Flush

Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Connections - terminals	Screw terminal
Embedding depth	20 mm
Number of terminals	6 20 A at 250 V AC, inductive 20 A at 250 V AC, resistive 250 V AC
Network frequency	50/60 Hz
Contacts material	Brass and phosphor bronze 6 screw terminals
Terminal identifier	L1 L2 N1 N2
Tightening torque	0.4 N.m
Clamping connection capacity	<= 4 mm ² for rigid or stranded cable(s)
Wire stripping length	12 mm
Width	86 mm
Height	86 mm
Depth	32 mm

Environment

Standards	IEC 60669-1 SS 227 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	123 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.054 kg

Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	10090 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Thay thế được đề xuất