

# 250V 16AX 1 Way Switch 2M Sized Module, Bronze

8431M\_1\_BZ

***

Range	ZENcelo
Product or component type	Switch
Load type	Resistive Capacitive Inductive
Colour tint	Bronze

### Complementary

Device mounting	Surface Flush
Switch function	1-way
Rated current	16 AX at 250 V AC 50/60 Hz
Local signalling	Indicator light, LED (amber)
Number of gangs	1 gang
Material	Brass: metal parts Polycarbonate: base Polycarbonate: dolly Polycarbonate: driver Polycarbonate + GF 20 %: actuator Polycarbonate: lenses
Connections - terminals	Clamp terminal
Width	34.85 mm
Height	45.8 mm
Depth	32.8 mm

### **Environment**

Environment	
Ambient air temperature for operation	-545 °C
Ambient air temperature for storage	-560 °C
Relative humidity	095 %
Environmental characteristic	UV resistant
Operating altitude	2000 m
Product certifications	CCC
Standards	GB 16915.1

	IEC 60669-1
IP degree of protection	IP20
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.495 cm
Package 1 Width	3.495 cm
Package 1 Length	4.56 cm
Package 1 Weight	25.7 g
Unit Type of Package 2	BB1
Number of Units in Package 2	16
Package 2 Height	7.5 cm
Package 2 Width	10 cm
Package 2 Length	15.5 cm
Package 2 Weight	453.9 g
Unit Type of Package 3	CAR
Number of Units in Package 3	160
Package 3 Height	16.5 cm
Package 3 Width	21 cm

## Offer Sustainability

Package 3 Length

Package 3 Weight

40 cm

4418 g

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

#### Recommended replacement(s)