

Bảng thông số sản phẩm

Thông số kỹ thuật



Zencelo - 250V 16A Twin 3 Pin UNI 3M sized SKT

84426LUES2_BZ_G19

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E universal
Load type	Inductive Resistive
Cover plate colour tint	Bronze

Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	2 gangs
Marking	L+N
Material	Polycarbonate base Polycarbonate cover
Connections - terminals	Screw terminals
Width	46 mm
Height	70.1 mm
Depth	30.5 mm

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %, non-condensing (storage) 10...95 %, non-condensing (operating)
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
IP degree of protection	IP20
Product certifications	TISI
Standards	IEC 60364 IEC 60884-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất