

# Product datasheet

Specifications



## Zencelo - 250V 16A SINGLE 3 PIN UNI 2M SIZED SKT

84426MUES\_WE\_G19

### Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P + E universal
Load type	Inductive Resistive
Cover plate colour tint	White

### Complementary

Device mounting	Flush Surface
Rated current	16 A at 250 V AC 50 Hz
Number of gangs	1 gang
Marking	L+N
Material	Polycarbonate base Polycarbonate cover
Connections - terminals	Screw terminals
Embedding depth	21.5 mm
Width	46 mm
Height	46.6 mm
Depth	30 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %, non-condensing (storage) 10...95 %, non-condensing (operating)
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
IP degree of protection	IP20
Product certifications	TISI
Standards	IEC 60884-1

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

### Recommended replacement(s)