

20A 1 Gang Full-Flat Double Pole Switch with Neon, Sliver Bronze

E8431D20_SZ

Range	ZENcelo
Product or component type	Switch
Load type	Inductive
Colour tint	Silver bronze
Cover frame colour tint	Silver bronze

Complementary

Device mounting	Surface Flush
Rated current	20 A at 250 V AC 50/60 Hz
Number of gangs	1 gang
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: dolly Polycarbonate: surround
Connections - terminals	Brass rod terminals
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	31.5 mm

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	095 %
Environmental characteristic	No UV resistant
Standards	IEC 60669-1 BS EN 60669-1 GB 16915.1 SS 227-1 MS IEC 60669-1

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	130.87 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty 18 months

Recommended replacement(s)