

Bảng thông số sản phẩm

Thông số kỹ thuật



1 GANG DATA CAT6 W. SHUTTER ON PLATE, SILVER SATIN

E8431RJS_6_SA_G19

Main

Range	ZENcelo
Product or component type	Data socket
Device application	Communication
Socket additional information	Shuttered
Colour tint	Silver satin

Complementary

Rated current	1.5 A
Communication network category	Data: 6e
Insulation resistance	≥ 200 MOhm
Contact resistance	1 μ Ohm
Number of gangs	1 gang
Minimum return loss	23 dB
AWG gauge	AWG 26...AWG 22 (4 twisted pair cables)
Contacts material	Housing: PC Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate: plastic part
Device mounting	Surface Flush
Width	87 mm
Height	87 mm
Depth	36 mm

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	1...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất