

Product datasheet

Specifications



10A 2 Gang Universal Socket, White

E84426U2_WE

Main

Range	ZENcelo
Product or component type	Power socket-outlet
Outlet poles configuration	2P
Load type	Resistive
Colour tint	White
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Rated current	10 A at 250 V AC 50 Hz
Number of gangs	2 gangs
Material	Polycarbonate base Polycarbonate grid plate Polycarbonate surround Brass contact plate Polycarbonate cover
Connections - terminals	Clamps terminal
Width	87 mm
Height	87 mm
Depth	27 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	IEC 60884-1 GB 2099.1 GB 2099.1 IEC 60884-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	135.8 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.286 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	13364 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)